



6 Outlet Surge Strip

Part No.	BB-30STR	BB-30STR-1L	BB-30STR-1B	BB-30STR-3B
Electrical rating	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W
Housing Material	Plastic	Plastic	Plastic	Plastic
AC Outlets	6	6	6	6
AC Outlet Type	Nema 5-15R	Nema 5-15R	Nema 5-15R	Nema 5-15R
Plug type	Nema 5-15P	Nema 5-15P	Nema 5-15P	Nema 5-15P
AC Cord Specs	SJT ; 14AWG	SJT ; 14AWG	SJT ; 14AWG	SJT ; 14AWG
Power Cord Length	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft
Overload Protection	15 Amps	15 Amps	15 Amps	15 Amps
Circuit Breaker Switch	Yes	Yes	Yes	Yes
Power Shutdown Protection	N/A	N/A	N/A	N/A
Max. Joules Rating	350 Joules	350 Joules	350 Joules	1050 Joules
Max. Spike Current	6500A	6500A	6500A	19500A
Max, Spike Voltage	6000V	6000V	6000V	6000V
Clamping Voltage (VPR)	400 (L-N)	400 (L-N)	400 (L-N)	400V (L-N) 500V(L-G, N-G)
Response Time	< 1 nanosecond	< 1 nanosecond	< 1 nanosecond	< 1 nanosecond
Surge Protection Indicator	N/A	Yes	N/A	Yes
Wire Fault Indicator	N/A	N/A	N/A	N/A
EMI/ RFI Noise Filter	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz	N/A	N/A	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz
USB Charger	N/A	N/A	N/A	N/A
Phone/Network Protector	RJ11: 1 in 2 out	RJ11: 1 in 2 out	RJ11: 1 in 2 out	RJ11: 1 in 2 out
Coax Protection	N/A	N/A	N/A	N/A
Product Dimension	L302.6 xW59.1xH47mm	L302.6 xW59.1xH47mm	L302.6 xW59.1xH47mm	L302.6 xW59.1xH47mm