



8 Outlet Yellow Strip

Part No.	CL-127	CL-127-1B	CL-127-3B
Electrical rating	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W
Housing Material	Steel	Steel	Steel
AC Outlets	8	8	8
AC Outlet Type	Nema 5-15R	Nema 5-15R	Nema 5-15R
Plug type	Nema 5-15P	Nema 5-15P	Nema 5-15P
AC Cord Specs	SJT; 14AWG	SJT; 14AWG	SJT; 14AWG
Power Cord Length	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft
Overload Protection	15 Amps	15 Amps	15 Amps
Circuit Breaker Switch	Lighted SW	Lighted SW	Lighted SW
Power Shutdown Protection	N/A	N/A	Yes
Max. Joules Rating	N/A	350 Joules	1050 Joules
Max. Spike Current	N/A	6500 Amps	19,500 Amps
Max, Spike Voltage	N/A	6000V	6000V
Clamping Voltage (VPR)	N/A	400V (L-N)	400V (L-N, N-G) 500V(L-G)
Response Time	N/A	< 1 nanosecond	< 1 nanosecond
Surge Protection Indicator	N/A	N/A	1*Red LED
Wire Fault Indicator	N/A	N/A	N/A
EMI/ RFI Noise Filter	N/A	N/A	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz
USB Charger	N/A	N/A	N/A
Phone/Network Protector	N/A	N/A	N/A
Coax Protection	N/A	N/A	N/A
Product Dimension	L256.5 xW172.6 x H48.6mm	L256.5 xW172.6 x H48.6mm	L256.5 xW172.6 x H48.6mm