



### 9 Outlet 19" Rack Mounted Surge Protector

Part No.	CL-130A	CL-130B
Electrical rating	125V/15A /1875W	125V/15A /1875W
Housing Material	Steel	Steel
AC Outlets	9	9
AC Outlet Type	Nema 5-15R	Nema 5-15R
Plug type	Nema 5-15P	L5-15P
AC Cord Specs	SJT ; 14AWG	SJT ; 14AWG
Power Cord Length	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft
Overload Protection	15 Amps	15 Amps
Circuit Breaker Switch	Yes	Yes
Power Shutdown Protection	Yes	Yes
Max. Joules Rating	2450 Joules	2450 Joules
Max. Spike Current	45500Amps	45500Amps
Max, Spike Voltage	6000V	6000V
Clamping Voltage (VPR)	400V (L-N) 500 (L-G, N-G)	400V (L-N) 500 (L-G, N-G)
Response Time	< 1 nanosecond	< 1 nanosecond
Surge Protection Indicator	1*Green LED	1*Green LED
Wire Fault Indicator	1*Green LED	1*Green LED
EMI/ RFI Noise Filter	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz
USB Charger (Option)	N/A	N/A
Phone/Network Protector	N/A	N/A
Coax Protection	N/A	N/A
Product Dimension	L481xW32xH114.4mm	L481xW32xH114.4mm