



6 Outlet Surge Protector

Part No.	FS-069B1	FS-069B2	FS-069B3
Electrical rating	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W
Housing Material	Plastic	Plastic	Plastic
AC Outlets	6	6	6
AC Outlet Type	Nema 5-15R	Nema 5-15R	Nema 5-15R
Plug type	Nema 5-15P	Nema 5-15P	Nema 5-15P
AC Cord Specs	SJT ; 14AWG	SJT ; 14AWG	SJT ; 14AWG
Power Cord Length	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft
Overload Protection	15 Amps	15 Amps	15 Amps
Circuit Breaker Switch	Lighted SW	Lighted SW	Lighted SW
Power Shutdown Protection	Yes	Yes	Yes
Max. Joules Rating	500 Joules	750 Joules	880 Joules
Max. Spike Current	9000 Amps	13500 Amps	19000 Amps
Max, Spike Voltage	6000V	6000V	6000V
Clamping Voltage (VPR)	500V(L-N, L-G)	500V(L-N, L-G, N-G)	330V (L-N) 500V(L-G, N-G)
Response Time	< 1 nanosecond	< 1 nanosecond	< 1 nanosecond
Surge Protection Indicator	Yes	Yes	Yes
Wire Fault Indicator	Yes	Yes	Yes
EMI/ RFI Noise Filter	Attenuation Up to 45 dB Freq. 150Khz to 30Mhz	Attenuation Up to 45 dB Freq. 150Khz to 30Mhz	Attenuation Up to 45 dB Freq. 150Khz to 30Mhz
USB Charger	N/A	N/A	N/A
Phone/Network Protector	N/A	N/A	N/A
Coax Protection	N/A	N/A	N/A
Product Dimension	L x W x Hmm	L x W x Hmm	L x W x Hmm



6 Outlet Surge Protector

Part No.	FS-069B4	FS-069B5	FS-069B6
Electrical rating	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W
Housing Material	Plastic	Plastic	Plastic
AC Outlets	8	8	8
AC Outlet Type	Nema 5-15R	Nema 5-15R	Nema 5-15R
Plug type	Nema 5-15P	Nema 5-15P	Nema 5-15P
AC Cord Specs	SJT ; 14AWG	SJT ; 14AWG	SJT ; 14AWG
Power Cord Length	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft
Overload Protection	15 Amps	15 Amps	15 Amps
Circuit Breaker Switch	Lighted SW	Lighted SW	Lighted SW
Power Shutdown Protection	Yes	Yes	Yes
Max. Joules Rating	1010 Joules	1140 Joules	1520 Joules
Max. Spike Current	24500 Amps	30000 Amps	40000Amps
Max, Spike Voltage	6000V	6000V	6000V
Clamping Voltage (VPR)	330V (L-N) 400V (L-G) 500V(N-G)	330V (L-N) 400V(L-G, N-G)	330V (L-N) 400V(L-G, N-G)
Response Time	< 1 nanosecond	< 1 nanosecond	< 1 nanosecond
Surge Protection Indicator	Yes	Yes	Yes
Wire Fault Indicator	Yes	Yes	Yes
EMI/ RFI Noise Filter	Attenuation Up to 45 dB Freq. 150Khz to 30Mhz	Attenuation Up to 45 dB Freq. 150Khz to 30Mhz	Attenuation Up to 45 dB Freq. 150Khz to 30Mhz
USB Charger	N/A	N/A	N/A
Phone/Network Protector	N/A	N/A	N/A
Coax Protection	N/A	N/A	N/A
Product Dimension	L x W x Hmm	L x W x Hmm	L x W x Hmm



6 Outlet Surge Protector

Part No.	FS-069C1	FS-069C2	FS-069C3
Electrical rating	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W
Housing Material	Plastic	Plastic	Plastic
AC Outlets	8	8	8
AC Outlet Type	Nema 5-15R	Nema 5-15R	Nema 5-15R
Plug type	Nema 5-15P	Nema 5-15P	Nema 5-15P
AC Cord Specs	SJT ; 14AWG	SJT ; 14AWG	SJT ; 14AWG
Power Cord Length	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft
Overload Protection	15 Amps	15 Amps	15 Amps
Circuit Breaker Switch	Lighted SW	Lighted SW	Lighted SW
Power Shutdown Protection	Yes	Yes	Yes
Max. Joules Rating	500 Joules	750 Joules	880 Joules
Max. Spike Current	9000 Amps	13500 Amps	19000Amps
Max, Spike Voltage	6000V	6000V	6000V
Clamping Voltage (VPR)	500V (L-N) 500V(L-G)	500V(L-G,L-N, N-G)	500V(L-G,L-N, N-G)
Response Time	< 1 nanosecond	< 1 nanosecond	< 1 nanosecond
Surge Protection Indicator	Yes	Yes	Yes
Wire Fault Indicator	Yes	Yes	Yes
EMI/ RFI Noise Filter	Attenuation Up to 45 dB Freq. 150Khz to 30Mhz	Attenuation Up to 45 dB Freq. 150Khz to 30Mhz	Attenuation Up to 45 dB Freq. 150Khz to 30Mhz
USB Charger	N/A	N/A	N/A
Phone/Network Protector	N/A	N/A	N/A
Coax Protection	F Connector	F Connector	F Connector
Product Dimension	L x W x Hmm	L x W x Hmm	L x W x Hmm



6 Outlet Surge Protector

Part No.	FS-069C4	FS-069C5	FS-069C6
Electrical rating	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W
Housing Material	Plastic	Plastic	Plastic
AC Outlets	8	8	8
AC Outlet Type	Nema 5-15R	Nema 5-15R	Nema 5-15R
Plug type	Nema 5-15P	Nema 5-15P	Nema 5-15P
AC Cord Specs	SJT ; 14AWG	SJT ; 14AWG	SJT ; 14AWG
Power Cord Length	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft
Overload Protection	15 Amps	15 Amps	15 Amps
Circuit Breaker Switch	Yes	Yes	Yes
Power Shutdown Protection	Yes	Yes	Yes
Max. Joules Rating	1010 Joules	1140 Joules	1520 Joules
Max. Spike Current	24500 Amps	30000 Amps	40000Amps
Max, Spike Voltage	6000V	6000V	6000V
Clamping Voltage (VPR)	330V (L-N) 400V (L-G) 500V(N-G)	330V (L-N) 400V(L-G, N-G)	330V (L-N) 400V(L-G, N-G)
Response Time	< 1 nanosecond	< 1 nanosecond	< 1 nanosecond
Surge Protection Indicator	Yes	Yes	Yes
Wire Fault Indicator	Yes	Yes	Yes
EMI/ RFI Noise Filter	Attenuation Up to 45 dB Freq. 150Khz to 30Mhz	Attenuation Up to 45 dB Freq. 150Khz to 30Mhz	Attenuation Up to 45 dB Freq. 150Khz to 30Mhz
USB Charger	N/A	N/A	N/A
Phone/Network Protector	N/A	N/A	N/A
Coax Protection	F Connector	F Connector	F Connector
Product Dimension	L x W x Hmm	L x W x Hmm	L x W x Hmm



6 Outlet Surge Protector

Part No.	FS-069D1	FS-069D2	FS-069D3
Electrical rating	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W
Housing Material	Plastic	Plastic	Plastic
AC Outlets	8	8	8
AC Outlet Type	Nema 5-15R	Nema 5-15R	Nema 5-15R
Plug type	Nema 5-15P	Nema 5-15P	Nema 5-15P
AC Cord Specs	SJT ; 14AWG	SJT ; 14AWG	SJT ; 14AWG
Power Cord Length	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft
Overload Protection	15 Amps	15 Amps	15 Amps
Circuit Breaker Switch	Yes	Yes	Yes
Power Shutdown Protection	Yes	Yes	Yes
Max. Joules Rating	500 Joules	750 Joules	880 Joules
Max. Spike Current	9000 Amps	13500 Amps	19000Amps
Max, Spike Voltage	6000V	6000V	6000V
Clamping Voltage (VPR)	500V(L-G, L-N)	500V(L-G,L-N, N-G)	330V (L-N) 500V(L-G, N-G)
Response Time	< 1 nanosecond	< 1 nanosecond	< 1 nanosecond
Surge Protection Indicator	Yes	Yes	Yes
Wire Fault Indicator	Yes	Yes	Yes
EMI/ RFI Noise Filter	Attenuation Up to 45 dB Freq. 150Khz to 30Mhz	Attenuation Up to 45 dB Freq. 150Khz to 30Mhz	Attenuation Up to 45 dB Freq. 150Khz to 30Mhz
USB Charger	N/A	N/A	N/A
Phone/Network Protector	RJ 11: 1 in 1 out	RJ 11: 1 in 1 out	RJ 11: 1 in 1 out
Coax Protection	N/A	N/A	N/A
Product Dimension	L x W x Hmm	L x W x Hmm	L x W x Hmm



6 Outlet Surge Protector

Part No.	FS-069D4	FS-069D5	FS-069D6
Electrical rating	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W
Housing Material	Plastic	Plastic	Plastic
AC Outlets	8	8	8
AC Outlet Type	Nema 5-15R	Nema 5-15R	Nema 5-15R
Plug type	Nema 5-15P	Nema 5-15P	Nema 5-15P
AC Cord Specs	SJT ; 14AWG	SJT ; 14AWG	SJT ; 14AWG
Power Cord Length	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft
Overload Protection	15 Amps	15 Amps	15 Amps
Circuit Breaker Switch	Yes	Yes	Yes
Power Shutdown Protection	Yes	Yes	Yes
Max. Joules Rating	1010 Joules	1140 Joules	1520 Joules
Max. Spike Current	24500 Amps	30000 Amps	40000Amps
Max, Spike Voltage	6000V	6000V	6000V
Clamping Voltage (VPR)	330V (L-N) ,400V(L-G) 500V (N-G)	330V (L-N) 400V(L-G, N-G)	330V (L-N) 400V(L-G, N-G)
Response Time	< 1 nanosecond	< 1 nanosecond	< 1 nanosecond
Surge Protection Indicator	Yes	Yes	Yes
Wire Fault Indicator	Yes	Yes	Yes
EMI/ RFI Noise Filter	Attenuation Up to 45 dB Freq. 150Khz to 30Mhz	Attenuation Up to 45 dB Freq. 150Khz to 30Mhz	Attenuation Up to 45 dB Freq. 150Khz to 30Mhz
USB Charger	N/A	N/A	N/A
Phone/Network Protector	RJ11: 1 in 1 out	RJ11: 1 in 1 out	RJ11: 1 in 1 out
Coax Protection	N/A	N/A	N/A
Product Dimension	L x W x Hmm	L x W x Hmm	L x W x Hmm