



### 4 Outlets Surge Protector W/2 USB Charger

Part No.	FS-072U	FS-072U-A1	FS-072U-A2	FS-072U-A3
Electrical rating	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W
Housing Material	Plastic	Plastic	Plastic	Plastic
AC Outlets	4	4	4	4
AC Outlet Type	Nema 5-15R	Nema 5-15R	Nema 5-15R	Nema 5-15R
Plug type	Nema 5-15P	Nema 5-15P	Nema 5-15P	Nema 5-15P
AC Cord Specs	SJT or SJT-B; 14AWG	SJT or SJT-B; 14AWG	SJT or SJT-B; 14AWG	SJT or SJT-B; 14AWG
Power Cord Length	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft
Overload Protection	15 Amps	15 Amps	15 Amps	15 Amps
Circuit Breaker Switch	Lighted SW	Lighted SW	Lighted SW	Lighted SW
Power Shutdown Protection	N/A	N/A	Yes	Yes
Max. Joules Rating	N/A	750 Joules	1250 Joules	1450 Joules
Max. Spike Current	N/A	13500A	22500A	29500A
Max, Spike Voltage	N/A	6000V	6000V	6000V
Clamping Voltage (VPR)	N/A	500 (L-N,L-G, N-G)	500 (L-N,L-G, N-G)	500 (L-N,L-G, N-G)
Response Time	N/A	< 1 nanosecond	< 1 nanosecond	< 1 nanosecond
Surge Protection Indicator	N/A	1*Green LED	1*Green LED	1*Green LED
EMI/ RFI Noise Filter	N/A	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz
USB Charger	2 x USB - 2.4A shared	2 x USB - 2.4A shared	2 x USB - 2.4A shared	2 x USB - 2.4A shared
Product Dimension	L276 x W47 x H32mm	L276 x W47 x H32mm	L276 x W47 x H32mm	L276 x W47 x H32mm