


### 6 Outlet Surge Protector

Part No.	BB-05	BB-05-1	BB-05-3	BB-05-5
Electrical rating	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W
Housing Material	Plastic	Plastic	Plastic	Plastic
AC Outlets	6	6	6	6
AC Outlet Type	Nema 5-15R	Nema 5-15R	Nema 5-15R	Nema 5-15R
Plug type	Nema 5-15P	Nema 5-15P	Nema 5-15P	Nema 5-15P
AC Cord Specs	SJT ; 14AWG	SJT ; 14AWG	SJT ; 14AWG	SJT ; 14AWG
Power Cord Length	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft
Overload Protection	15 Amps	15 Amps	15 Amps	15 Amps
Circuit Breaker Switch	N/A	N/A	Lighted SW	Lighted SW
Power Shutdown Protection	N/A	N/A	Yes	Yes
Max. Joules Rating	N/A	250 Joules	750 Joules	750 Joules
Max. Spike Current	N/A	4500A	13500A	13500A
Max, Spike Voltage	N/A	6000V	6000V	6000V
Clamping Voltage (VPR)	N/A	500 (L-N)	500 (L-N,L-G, N-G)	500 (L-N,L-G, N-G)
Response Time	N/A	< 1 nanosecond	< 1 nanosecond	< 1 nanosecond
Surge Protection Indicator	N/A	N/A	Yes	Yes
Wire Fault Indicator	N/A	N/A	N/A	N/A
EMI/ RFI Noise Filter	N/A	N/A	N/A	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz
USB Charger	N/A	N/A	N/A	N/A
Phone/Network Protector	N/A	N/A	N/A	N/A
Coax Protection	N/A	N/A	N/A	N/A
Product Dimension	L246.5xW47x H35.2mm	L246.5xW47x H35.2mm	L246.5xW47x H35.2mm	L246.5xW47x H35.2mm



### 6 Outlet Surge Protector

Part No.	BB-05-1B	BB-05-1S	BB-05-4B	
Electrical rating	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W	
Housing Material	Plastic	Plastic	Plastic	
AC Outlets	6	6	6	
AC Outlet Type	Nema 5-15R	Nema 5-15R	Nema 5-15R	
Plug type	Nema 5-15P	Nema 5-15P	Nema 5-15P	
AC Cord Specs	SJT ; 14AWG	SJT ; 14AWG	SJT ; 14AWG	
Power Cord Length	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	
Overload Protection	15 Amps	15 Amps	15 Amps	
Circuit Breaker Switch	Yes	Yes	Yes	
Power Shutdown Protection	N/A	Yes	Yes	
Max. Joules Rating	350 Joules	250 Joules	1000 Joules	
Max. Spike Current	6500A	4500A	18000A	
Max, Spike Voltage	6000V	6000V	6000V	
Clamping Voltage (VPR)	500V (L-N)	500V (L-N)	500V (L-N,L-G, N-G)	
Response Time	< 1 nanosecond	< 1 nanosecond	< 1 nanosecond	
Surge Protection Indicator	N/A	Yes	Yes	
Wire Fault Indicator	N/A	N/A	N/A	
EMI/ RFI Noise Filter	N/A	N/A	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz	
USB Charger	N/A	N/A	N/A	
Phone/Network Protector	N/A	N/A	N/A	
Coax Protection	N/A	N/A	N/A	
Product Dimension	L246.5xW47x H35.2mm	L246.5xW47x H35.2mm	L246.5xW47x H35.2mm	