



6 Outlet Surge Protector

Part No.	BB-30	BB-30-1	BB-30-1L	BB-30-3	BB-30-5
Electrical rating	120V/15A /1800W	120V/15A /1800W	120V/15A /1800W	120V/15A /1800W	120V/15A /1800W
Housing Material	Plastic	Plastic	Plastic	Plastic	Plastic
AC Outlets	6	6	6	6	6
AC Outlet Type	Nema 5-15R	Nema 5-15R	Nema 5-15R	Nema 5-15R	Nema 5-15R
Plug type	Nema 5-15P	Nema 5-15P	Nema 5-15P	Nema 5-15P	Nema 5-15P
AC Cord Specs	SJT ; 14AWG	SJT ; 14AWG	SJT ; 14AWG	SJT ; 14AWG	SJT ; 14AWG
Power Cord Length	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft
Overload Protection	15 Amps	15 Amps	15 Amps	15 Amps	15 Amps
Circuit Breaker Switch	Lighted SW	Lighted SW	Lighted SW	Lighted SW	Lighted SW
Power Shutdown Protection	N/A	N/A	N/A	Yes	N/A
Max. Joules Rating	N/A	250 Joules	250 Joules	750 Joules	750 Joules
Max. Spike Current	N/A	6500A	6500A	19500A	6500A
Max, Spike Voltage	N/A	6000V	6000V	6000V	6000V
Clamping Voltage (VPR)	N/A	400 (L-N)	400 (L-N)	400V (L-N, N-G) 500V(L-G)	400V (L-N, N-G) 500V(L-G)
Response Time	N/A	< 1 nanosecond	< 1 nanosecond	< 1 nanosecond	< 1 nanosecond
Surge Protection Indicator	N/A	N/A	1*Red LED	1*Red LED	1*Red LED
Wire Fault Indicator	N/A	N/A	N/A	N/A	
EMI/ RFI Noise Filter	N/A	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz
USB Charger	N/A	N/A	N/A	N/A	N/A
Phone/Network Protector	N/A	N/A	N/A	N/A	N/A
Coax Protection	N/A	N/A	N/A	N/A	N/A
Product Dimension	L260 x W47 x H48mm	L260 x W47 x H48mm	L260 x W47 x H48mm	L260 x W47 x H48mm	L260 x W47 x H48mm