



### 6 Outlet Surge Strip

Part No.	BB-30STA	BB-30STA-1L	BB-30STA-1B	BB-30STA-3B
Electrical rating	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W
Housing Material	Plastic	Plastic	Plastic	Plastic
AC Outlets	6	6	6	6
AC Outlet Type	shockless	shockless	shockless	shockless
Plug type	Nema 5-15P	Nema 5-15P	Nema 5-15P	Nema 5-15P
AC Cord Specs	SJT ; 14AWG	SJT ; 14AWG	SJT ; 14AWG	SJT ; 14AWG
Power Cord Length	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft
Overload Protection	15 Amps	15 Amps	15 Amps	15 Amps
Circuit Breaker Switch	Yes	Yes	Yes	Yes
Power Shutdown Protection	N/A	N/A	N/A	Yes
Max. Joules Rating	350 Joules	350 Joules	350 Joules	1050 Joules
Max. Spike Current	6500A	6500A	6500A	19500A
Max, Spike Voltage	6000V	6000V	6000V	6000V
Clamping Voltage (VPR)	400V (L-N)	400V (L-N)	400V (L-N)	400V ( L-N) 500V( L-G, N-G)
Response Time	< 1 nanosecond	< 1 nanosecond	< 1 nanosecond	< 1 nanosecond
Surge Protection Indicator	N/A	Yes	Yes	Yes
Wire Fault Indicator	N/A	N/A	N/A	N/A
EMI/ RFI Noise Filter	N/A	N/A	N/A	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz
USB Charger	N/A	N/A	N/A	N/A
Phone/Network Protector	N/A	N/A	N/A	N/A
Coax Protection	F Connector	N/A	F Connector	F Connector
Product Dimension	L302.6 xW59.1xH47mm	L302.6 xW59.1xH47mm	L302.6 xW59.1xH47mm	L302.6 xW59.1xH47mm