


7 Outlets Surge Protector

Part No.	BB-53	BB-53-1B	BB-53-3B	BB-53-7B
Electrical rating	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W
Housing Material	Plastic	Plastic	Plastic	Plastic
AC Outlets	7	7	7	7
AC Outlet Type	Nema 5-15R	Nema 5-15R	Nema 5-15R	Nema 5-15R
Plug type	Nema 5-15P	Nema 5-15P	Nema 5-15P	Nema 5-15P
AC Cord Specs	SJT ; 14AWG	SJT ; 14AWG	SJT ; 14AWG	SJT ; 14AWG
Power Cord Length	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft
Overload Protection	15 Amps	15 Amps	15 Amps	15 Amps
Circuit Breaker Switch	Lighted SW	Lighted SW	Lighted SW	Lighted SW
Power Shutdown Protection	N/A	Yes	Yes	Yes
Max. Joules Rating	N/A	350 Joules	1050 Joules	2450 Joules
Max. Spike Current	N/A	6500A	19500A	45500A
Max, Spike Voltage	N/A	6000V	6000V	6000V
Clamping Voltage (VPR)	N/A	400V (L-N,L-G,N-G)	400V (L-N,L-G,N-G)	400V (L-N,L-G,N-G)
Response Time	N/A	< 1 nanosecond	< 1 nanosecond	< 1 nanosecond
Surge Protection Indicator	N/A	N/A	1*Red LED	1*Red LED
Grounded Indicator	N/A	N/A	1*Green LED	1*Green LED
EMI/ RFI Noise Filter	N/A	N/A	Attenuation up to 20 dB Freq. 150Khz to 30Mhz	Attenuation up to 20 dB Freq. 150Khz to 30Mhz
USB Charger	N/A	N/A	N/A	N/A
Phone/Network Protector	N/A	N/A	N/A	N/A
Coax Protection	N/A	N/A	N/A	N/A
Product Dimension	L332xW62x H38mm	L332xW62x H38mm	L332xW62x H38mm	L332xW62x H38mm



7 Outlets Surge Protector

Part No.	BB-53R-3B	BB-53R-7B	BB-53A-3B	BB-53A-7B
Electrical rating	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W
Housing Material	Plastic	Plastic	Plastic	Plastic
AC Outlets	7	7	7	7
AC Outlet Type	Nema 5-15R	Nema 5-15R	Nema 5-15R	Nema 5-15R
Plug type	Nema 5-15P	Nema 5-15P	Nema 5-15P	Nema 5-15P
AC Cord Specs	SJT ; 14AWG	SJT ; 14AWG	SJT ; 14AWG	SJT ; 14AWG
Power Cord Length	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft
Overload Protection	15 Amps	15 Amps	15 Amps	15 Amps
Circuit Breaker Switch	Lighted SW	Lighted SW	Lighted SW	Lighted SW
Power Shutdown Protection	Yes	Yes	Yes	Yes
Max. Joules Rating	1050 Joules	2450 Joules	1050 Joules	2450 Joules
Max. Spike Current	19500A	45500A	19500A	45500A
Max, Spike Voltage	6000V	6000V	6000V	6000V
Clamping Voltage (VPR)	400V (L-N,L-G,N-G)	400V (L-N,L-G,N-G)	400V (L-N,L-G,N-G)	400V (L-N,L-G,N-G)
Response Time	< 1 nanosecond	< 1 nanosecond	< 1 nanosecond	< 1 nanosecond
Surge Protection Indicator	1*Red LED	1*Red LED	1*Red LED	1*Red LED
Grounded Indicator	1*Green LED	1*Green LED	1*Green LED	1*Green LED
EMI/ RFI Noise Filter	Attenuation up to 20 dB Freq. 150Khz to 30Mhz	Attenuation up to 20 dB Freq. 150Khz to 30Mhz	Attenuation up to 20 dB Freq. 150Khz to 30Mhz	Attenuation up to 20 dB Freq. 150Khz to 30Mhz
USB Charger	N/A	N/A	N/A	N/A
Phone/Network Protector	RJ11: 1 in - 2 out	RJ11: 1 in - 2 out	N/A	N/A
Coax Protection	N/A	N/A	F connector	F connector
Satellite Protection	N/A	N/A	N/A	N/A
Product Dimension	L332xW62x H38mm	L332xW62x H38mm	L332xW62x H38mm	L332xW62x H38mm