



**6 Outlets Surge Protector
6 Outlets Surge Protector With 2 USB Charger**

Part No.	BB-57-4B	BB-57-6B	BB-57U	BB-57U-4B	BB-57U-6B
Electrical rating	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W
Housing Material	Plastic	Plastic	Plastic	Plastic	Plastic
AC Outlets	6	6	6	6	6
AC Outlet Type	Nema 5-15R	Nema 5-15R	Nema 5-15R	Nema 5-15R	Nema 5-15R
Plug type	Nema 5-15P	Nema 5-15P	Nema 5-15P	Nema 5-15P	Nema 5-15P
AC Cord Specs	SJT ; 14AWG	SJT ; 14AWG	SJT ; 14AWG	SJT ; 14AWG	SJT ; 14AWG
Power Cord Length	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft
Overload Protection	15 Amps	15 Amps	15 Amps	15 Amps	15 Amps
Circuit Breaker Switch	Yes	Yes	Yes	Yes	Yes
Power Shutdown Protection	Yes	Yes	N/A	Yes	Yes
Max. Joules Rating	1400 Joules	2100 Joules	N/A	1400 Joules	2100 Joules
Max. Spike Current	19500A	39000A	N/A	19500A	39000A
Max. Spike Voltage	6000V	6000V	N/A	6000V	6000V
Clamping Voltage (VPR)	400V (L-N,L-G, N-G)	400V (L-N,L-G, N-G)	N/A	400V (L-N,L-G, N-G)	400V (L-N,L-G, N-G)
Response Time	< 1 nanosecond	< 1 nanosecond	N/A	< 1 nanosecond	< 1 nanosecond
Surge Protection Indicator	1*Green LED	1*Green LED	N/A	1*Green LED	1*Green LED
Wire Fault Indicator	1*Red LED	1*Red LED	N/A	1*Red LED	1*Red LED
EMI/ RFI Noise Filter	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz	N/A	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz
USB Charger	N/A	N/A	2 x USB - 2.4A shared	2 x USB - 2.4A shared	2 x USB - 2.4A shared
Phone/Network Protector	N/A	N/A	N/A	N/A	N/A
Coax Protection	N/A	N/A	N/A	N/A	N/A
Product Dimension	L344.8xW73.5x H73mm	L344.8xW73.5x H73mm	L344.8xW73.5x H73mm	L344.8xW73.5x H73mm	L344.8xW73.5x H73mm