



### 3 Outlet Traveler's Surge Protector

Part No.	BB-59U	BB-59U-3B
Electrical rating	125V/15A /1875W	125V/15A /1875W
Housing Material	Plastic	Plastic
AC Outlets	3	3
AC Outlet Type	Nema 5-15R	Nema 5-15R
Plug type	Nema 5-15P	Nema 5-15P
AC Cord Specs	SJT ; 14AWG	SJT ; 14AWG
Power Cord Length	Min.1.5ft~ Max.25ft	Min.1.5ft~Max.25ft
Overload Protection	15 Amps	15 Amps
Circuit Breaker Switch	N/A	N/A
Power Shutdown Protection	N/A	Yes
Max. Joules Rating	N/A	1050 Joules
Max. Spike Current	N/A	19500 Amps
Max, Spike Voltage	N/A	6000V
Clamping Voltage (VPR)	N/A	400V ( L-N,L-G,N-G)
Response Time	N/A	< 1 nanosecond
Surge Protection Indicator	N/A	1*Red LED
Wire Fault Indicator	N/A	N/A
EMI/ RFI Noise Filter	N/A	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz
USB Charger	2 x USB - 2.4A shared	2 x USB - 2.4A shared
Phone/Network Protector	N/A	N/A
Coax Protection	N/A	N/A
Product Dimension	L114.6 x W75 x H35.6mm	L114.6 x W75 x H35.6mm