



6 Outlet Metal Surge Protector

Part No.	CL-106-SWCB	CL-106-3B	CL-106-6B
Electrical rating	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W
Housing Material	Plastic	Steel	Steel
AC Outlets	6	6	6
AC Outlet Type	Nema 5-15R	Nema 5-15R	Nema 5-15R
Plug type	Nema 5-15P	Nema 5-15P	Nema 5-15P
AC Cord Specs	SJT ; 14AWG	SJT ; 14AWG	SJT ; 14AWG
Power Cord Length	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft
Overload Protection	15 Amps	15 Amps	15 Amps
Circuit Breaker Switch	Lighted SW	Lighted SW	Lighted SW
Power Shutdown Protection	N/A	Yes	Yes
Max. Joules Rating	N/A	1050 Joules	2100 Joules
Max. Spike Current	N/A	19,500 Amps	39,000Amps
Max, Spike Voltage	N/A	6000V	6000V
Clamping Voltage (VPR)	N/A	400V (L-N, L-G, N-G)	400V (L-N, L-G, N-G)
Response Time	N/A	< 1 nanosecond	< 1 nanosecond
Surge Protection Indicator	N/A	1*Red LED	1*Red LED
Wire Fault Indicator	N/A	N/A	N/A
EMI/ RFI Noise Filter	N/A	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz
USB Charger	N/A	N/A	N/A
Phone/Network Protector	N/A	N/A	N/A
Coax/Satellite Protection	N/A	N/A	N/A
Product Dimension	L310 x W62 x H34.8mm	L310 x W62 x H34.8mm	L310 x W62 x H34.8mm