



6 Outlet Surge Protector

Part No.	CL-208	CL-208AV	CL-208RJS
Electrical rating	120V/15A /1800W	120V/15A /1800W	120V/15A /1800W
Housing Material	Plastic	Plastic	Plastic
AC Outlets	6	6	6
AC Outlet Type	Nema 5-15R	Nema 5-15R	Nema 5-15R
Plug type	Nema 5-15P	Nema 5-15P	Nema 5-15P
AC Cord Specs	SJT; 14AWG	SJT; 14AWG	SJT; 14AWG
Power Cord Length	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft
Overload Protection	15 Amps	15 Amps	15 Amps
Circuit Breaker Switch	Lighted SW	Lighted SW	Lighted SW
Power Shutdown Protection	Yes	Yes	Yes
Max. Joules Rating	750 Joules	750 Joules	750 Joules
Max. Spike Current	13500 Amps	13500 Amps	13500 Amps
Max, Spike Voltage	6000V	6000V	6000V
Clamping Voltage (VPR)	400V (L-N,N-G) 500V(L-G)	400V (L-N,N-G) 500V(L-G)	400V (L-N, N-G) 500V(L-G)
Response Time	< 1 nanosecond	< 1 nanosecond	< 1 nanosecond
Surge Protection Indicator	1*Green LED	1*Green LED	1*Green LED
Wire Fault Indicator	1*Red LED	1*Red LED	1*Red LED
EMI/ RFI Noise Filter	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz
USB Charger	N/A	N/A	N/A
Phone/Network Protector	N/A	N/A	RJ11 : 1 in-1 out
Coax/Satellite Protection	N/A	F connector	N/A
Product Dimension	L200 x W85 xH34.6mm	L200 x W85 xH34.6mm	L200 x W85 xH34.6mm