



3 Outlet Wall Tap

Part No.	FA-356	FA-356-A	FA-356-B
Electrical rating	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W
Housing Material	Plastic	Plastic	Plastic
AC Outlets	3	3	3
AC Outlet Type	Nema 5-15R	Nema 5-15R	Nema 5-15R
Plug type	Nema 5-15P	Nema 5-15P	Nema 5-15P
Overload Protection	15 Amps	15 Amps	15 Amps
Power Shutdown Protection	Yes	Yes	Yes
Max. Joules Rating	500 Joules	750 Joules	980 Joules
Max. Spike Current	9000 Amps	13500 Amps	19000Amps
Max, Spike Voltage	6000V	6000V	6000V
Clamping Voltage (VPR)	500V(L-N, L-G)	500V(L-N, L-G,N-G)	400V (L-G) 500V(L-N, N-G)
Response Time	< 1 nanosecond	< 1 nanosecond	< 1 nanosecond
Surge Protection Indicator	Yes	Yes	Yes
Wire Fault Indicator	Yes	Yes	Yes
EMI/ RFI Noise Filter	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz
USB Charger	N/A	N/A	N/A
Phone/Network Protector	N/A	N/A	N/A
Coax/Satellite Protection	N/A	N/A	N/A
Product Dimension	L108 x W62.4 x 54.5Hmm	L108 x W62.4 x 54.5Hmm	L108 x W62.4 x 54.5Hmm