



### 5 Outlet Wall Tap

Part No.	FA-358	FA-358-A	FA-358-B	FA-358-C	FA-358-D
<b>Electrical rating</b>	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W
<b>Housing Material</b>	Plastic	Plastic	Plastic	Plastic	Plastic
<b>AC Outlets</b>	5	5	5	5	5
<b>AC Outlet Type</b>	Nema 5-15R	Nema 5-15R	Nema 5-15R	Nema 5-15R	Nema 5-15R
<b>Plug type</b>	Nema 5-15P	Nema 5-15P	Nema 5-15P	Nema 5-15P	Nema 5-15P
<b>Overload Protection</b>	15 Amps	15 Amps	15 Amps	15 Amps	15 Amps
<b>Power Shutdown Protection</b>	Yes	Yes	Yes	Yes	Yes
<b>Max. Joules Rating</b>	500 Joules	750 Joules	750 Joules	1210 Joules	1440 Joules
<b>Max. Spike Current</b>	9000A	13500A	13500A	24500A	30000A
<b>Max. Spike Voltage</b>	6000V	6000V	6000V	6000V	6000V
<b>Clamping Voltage (VPR)</b>	500V (L-N,L-G)	500 (L-N,L-G, N-G)	500 (L-N,L-G, N-G)	500 (L-N,L-G, N-G)	500 (L-N,L-G, N-G)
<b>Response Time</b>	< 1 nanosecond	< 1 nanosecond	< 1 nanosecond	< 1 nanosecond	< 1 nanosecond
<b>Surge Protection Indicator</b>	Yes	Yes	Yes	Yes	Yes
<b>Wire Fault Indicator</b>	Yes	Yes	Yes	Yes	Yes
<b>EMI/ RFI Noise Filter</b>	Attenuation Up to 45 dB Freq. 150Khz to 30Mhz	Attenuation Up to 45 dB Freq. 150Khz to 30Mhz	Attenuation Up to 45 dB Freq. 150Khz to 30Mhz	Attenuation Up to 45 dB Freq. 150Khz to 30Mhz	Attenuation Up to 45 dB Freq. 150Khz to 30Mhz
<b>USB Charger</b>	N/A	N/A	N/A	N/A	N/A
<b>Phone/Network Protector</b>	N/A	RJ11 : 1 in-1 out	N/A	N/A	N/A
<b>Coax Protection</b>	N/A	N/A	N/A	N/A	N/A
<b>Product Dimension</b>	L99xW127.8x H54mm	L99xW127.8x H54mm	L99xW127.8x H54mm	L99xW127.8x H54mm	L99xW127.8x H54mm