



6 Outlets Side Entry W/2 USB Charger

Part No.	FA-365U	FA-365U-1B	FA-365U-3B
Electrical rating	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W
Housing Material	Plastic	Plastic	Plastic
AC Outlets	6	6	6
AC Outlet Type	Nema 5-15R	Nema 5-15R	Nema 5-15R
Plug type	Nema 5-15P	Nema 5-15P	Nema 5-15P
Power Shutdown Protection	N/A	N/A	Yes
Max. Joules Rating	N/A	350 Joules	1050 Joules
Max. Spike Current	N/A	6500 Amps	19500 Amps
Max, Spike Voltage	N/A	6000V	6000V
Clamping Voltage (VPR)	N/A	500V (L-N)	500V (L-N, L-G, N-G)
Response Time	N/A	< 1 nanosecond	< 1 nanosecond
Surge Protection Indicator	N/A	1*Green LED	1*Green LED
Wire Fault Indicator	N/A	N/A	1*Green LED
EMI/ RFI Noise Filter	N/A	N/A	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz;
USB Charger	2 x USB - 3.4A shared	2 x USB - 3.4A shared	2 x USB - 3.4A shared
Product Dimension	L126 x W83 x H40mm	L126 x W83 x H40mm	L126 x W83 x H40mm