



### 7 Outlet Surge Protector (1 Transformer outlets)

Part No.	FS-041-A (94115)	FS-041-B (94116)	FS-041-C (94117)	FS-041-D (94118)	FS-041-E (94120)
<b>Electrical rating</b>	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W
<b>Housing Material</b>	Plastic	Plastic	Plastic	Plastic	Plastic
<b>AC Outlets</b>	7	7	7	7	7
<b>AC Outlet Type</b>	Nema 5-15R	Nema 5-15R	Nema 5-15R	Nema 5-15R	Nema 5-15R
<b>Plug type</b>	Nema 5-15P	Nema 5-15P	Nema 5-15P	Nema 5-15P	Nema 5-15P
<b>AC Cord Specs</b>	SJT ; 14AWG	SJT ; 14AWG	SJT ; 14AWG	SJT ; 14AWG	SJT ; 14AWG
<b>Power Cord Length</b>	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft
<b>Overload Protection</b>	15 Amps	15 Amps	15 Amps	15 Amps	15 Amps
<b>Circuit Breaker Switch</b>	Lighted SW	Lighted SW	Lighted SW	Lighted SW	Lighted SW
<b>Power Shutdown Protection</b>	Yes	Yes	Yes	Yes	Yes
<b>Max. Joules Rating</b>	1050 Joules	1050 Joules	1050 Joules	1650 Joules	1650 Joules
<b>Max. Spike Current</b>	13500A	13500A	13500A	29500A	29500A
<b>Max, Spike Voltage</b>	6000V	6000V	6000V	6000V	6000V
<b>Clamping Voltage (VPR)</b>	400V (L-N,L-G, N-G)	400V (L-N,L-G, N-G)	400V (L-N,L-G, N-G)	400V (L-N,L-G, N-G)	400V (L-N,L-G, N-G)
<b>Response Time</b>	< 1 nanosecond	< 1 nanosecond	< 1 nanosecond	< 1 nanosecond	< 1 nanosecond
<b>Surge Protection Indicator</b>	Yes	Yes	Yes	Yes	Yes
<b>Wire Fault Indicator</b>	Yes	Yes	Yes	Yes	Yes
<b>EMI/ RFI Noise Filter</b>	Attenuation Up to 45 dB Freq. 150Khz to 30Mhz	Attenuation Up to 45 dB Freq. 150Khz to 30Mhz	Attenuation Up to 45 dB Freq. 150Khz to 30Mhz	Attenuation Up to 45 dB Freq. 150Khz to 30Mhz	Attenuation Up to 45 dB Freq. 150Khz to 30Mhz
<b>USB Charger</b>	N/A	N/A	N/A	N/A	N/A
<b>Phone/Network Protector</b>	N/A	RJ11 : 1 in-2 out	N/A	N/A	N/A
<b>Coax Protection</b>	N/A	N/A	F Connector	N/A	F Connector
<b>Product Dimension</b>	LxWx Hmm	LxWx Hmm	LxWx Hmm	LxWx Hmm	LxWx Hmm



### 7 Outlet Surge Protector (1 Transformer outlets)

Part No.	FS-041-F (94121)	FS-041-G (94041)			
Electrical rating	125V/15A /1875W	125V/15A /1875W			
Housing Material	Plastic	Plastic			
AC Outlets	7	7			
AC Outlet Type	Nema 5-15R	Nema 5-15R			
Plug type	Nema 5-15P	Nema 5-15P			
AC Cord Specs	SJT ; 14AWG	SJT ; 14AWG			
Power Cord Length	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft			
Overload Protection	15 Amps	15 Amps			
Circuit Breaker Switch	Lighted SW	Lighted SW			
Power Shutdown Protection	Yes	Yes			
Max. Joules Rating	2100 Joules	1650 Joules			
Max. Spike Current	39000A	29500A			
Max, Spike Voltage	6000V	6000V			
Clamping Voltage (VPR)	400V (L-N,L-G, N-G)	400V (L-N,L-G, N-G)			
Response Time	< 1 nanosecond	< 1 nanosecond			
Surge Protection Indicator	Yes	Yes			
Wire Fault Indicator	Yes	Yes			
EMI/ RFI Noise Filter	Attenuation Up to 45 dB Freq. 150Khz to 30Mhz	Attenuation Up to 45 dB Freq. 150Khz to 30Mhz			
USB Charger	N/A	N/A			
Phone/Network Protector	N/A	RJ11 : 1 in-1 out			
Coax Protection	F Connector	N/A			
Product Dimension	LxWx Hmm	LxWx Hmm			