



6 Outlet Surge Protector

Part No.	FS-071U	FS-071UA1	FS-071UA2	FS-071UA3
Electrical rating	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W
Housing Material	Plastic	Plastic	Plastic	Plastic
AC Outlets	6	6	6	6
AC Outlet Type	Nema 5-15R	Nema 5-15R	Nema 5-15R	Nema 5-15R
Plug type	Nema 5-15P	Nema 5-15P	Nema 5-15P	Nema 5-15P
AC Cord Specs	SJT ; 14AWG	SJT ; 14AWG	SJT ; 14AWG	SJT ; 14AWG
Power Cord Length	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft
Overload Protection	15 Amps	15 Amps	15 Amps	15 Amps
Circuit Breaker Switch	Lighted SW	Yes	Yes	Yes
Power Shutdown Protection	N/A	Yes	Yes	Yes
Max. Joules Rating	N/A	750 Joules	1250 Joules	1310 Joules
Max. Spike Current	N/A	13500 Amps	22500 Amps	24500 Amps
Max, Spike Voltage	N/A	6000V	6000V	6000V
Clamping Voltage (VPR)	N/A	500V(L-N,L-G,N-G)	500V(L-N,L-G,N-G)	500V(L-N,L-G,N-G)
Response Time	N/A	< 1 nanosecond	< 1 nanosecond	< 1 nanosecond
Surge Protection Indicator	N/A	Yes	Yes	Yes
Wire Fault Indicator		N/A	N/A	N/A
EMI/ RFI Noise Filter	N/A	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz
USB Charger	2xUSB-2.4A	2xUSB-2.4A	2xUSB-2.4A	2xUSB-2.4A
Phone/Network Protector	N/A	N/A	N/A	N/A
Coax Protection	N/A	N/A	N/A	N/A
Product Dimension	LxWx Hmm	L x W x Hmm	L x W x Hmm	L x W x Hmm



6 Outlet Surge Protector

Part No.	FS-071UB1	FS-071UB2	FS-071UB3	
Electrical rating	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W	
Housing Material	Plastic	Plastic	Plastic	
AC Outlets	6	6	6	
AC Outlet Type	Nema 5-15R	Nema 5-15R	Nema 5-15R	
Plug type	Nema 5-15P	Nema 5-15P	Nema 5-15P	
AC Cord Specs	SJT ; 14AWG	SJT ; 14AWG	SJT ; 14AWG	
Power Cord Length	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	
Overload Protection	15 Amps	15 Amps	15 Amps	
Circuit Breaker Switch	Yes	Yes	Yes	
Power Shutdown Protection	Yes	Yes	Yes	
Max. Joules Rating	750 Joules	1250 Joules	1310 Joules	
Max. Spike Current	13500 Amps	22500 Amps	24500 Amps	
Max, Spike Voltage	6000V	6000V	6000V	
Clamping Voltage (VPR)	500V(L-N,L-G,N-G)	500V(L-N,L-G,N-G)	500V(L-N,L-G,N-G)	
Response Time	< 1 nanosecond	< 1 nanosecond	< 1 nanosecond	
Surge Protection Indicator	Yes	Yes	Yes	
Wire Fault Indicator	N/A	N/A	N/A	
EMI/ RFI Noise Filter	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz	
USB Charger	2xUSB-2.4A	2xUSB-2.4A	2xUSB-2.4A	
Phone/Network Protector	N/A	N/A	N/A	
Coax Protection	RJ11: 1 in-1 out	RJ11: 1 in-1 out	RJ11: 1 in-1 out	
Product Dimension	L x W x Hmm	L x W x Hmm	L x W x Hmm	