



### Metal Surge Protector With 2 USB Charger and 5 Outlets

Part No.	FS-086U	FS-086U-1B	FS-086U-3B	FS-086U-6B
Electrical rating	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W
Housing Material	Metal / Plastic	Metal / Plastic	Metal / Plastic	Metal / Plastic
AC Outlets	5	5	5	5
AC Outlet Type	Nema 5-15R	Nema 5-15R	Nema 5-15R	Nema 5-15R
Plug type	Nema 5-15P	Nema 5-15P	Nema 5-15P	Nema 5-15P
AC Cord Specs	SJT or SJT-B; 14AWG	SJT or SJT-B; 14AWG	SJT or SJT-B; 14AWG	SJT or SJT-B; 14AWG
Power Cord Length	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft
Overload Protection	15 Amps	15 Amps	15 Amps	15 Amps
Circuit Breaker Switch	Lighted SW	Lighted SW	Lighted SW	Lighted SW
Power Shutdown Protection	N/A	N/A	Yes	Yes
Max. Joules Rating	N/A	350 Joules	1050 Joules	2100 Joules
Max. Spike Current	N/A	6500 Amps	19500 Amps	39000Amps
Max. Spike Voltage	N/A	6000V	6000V	6000V
Clamping Voltage (VPR)	N/A	500V (L-N)	400V(L-N) 500V(L-G,N-G)	400V(L-N) 500V(L-G,N-G)
Response Time	N/A	< 1 nanosecond	< 1 nanosecond	< 1 nanosecond
Surge Protection Indicator	N/A	1*Green LED	1*Green LED	1*Green LED
Wire Fault Indicator	N/A	N/A	1*Green LED	1*Green LED
EMI/ RFI Noise Filter	N/A	N/A	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz	Attenuation Up to 20 dB Freq. 150Khz to 30Mhz
USB Charger (Option)	2 x USB - 2.4A shared	2 x USB - 2.4A shared	2 x USB - 2.4A shared	2 x USB - 2.4A shared
	2 x USB - 3.4A shared	2 x USB - 3.4A shared	2 x USB - 3.4A shared	2 x USB - 3.4A shared
Product Dimension	L315 x W70 x H36.3mm	L315 x W70 x H36.3mm	L315 x W70 x H36.3mm	L315 x W70 x H36.3mm