



3 Outlets Surge Protector With 2 USB Charger

Part No.	FS-088U	FS-088U-A1	FS-088U-A2
Electrical rating	125V/15A /1875W	125V/15A /1875W	125V/15A /1875W
Housing Material	Platic	Platic	Platic
AC Outlets	3	3	3
AC Outlet Type	Nema 5-15R	Nema 5-15R	Nema 5-15R
Plug type	Nema 5-15P	Nema 5-15P	Nema 5-15P
AC Cord Specs	SJT or SJT-B; 14AWG	SJT or SJT-B; 14AWG	SJT or SJT-B; 14AWG
Power Cord Length	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft	Min.1.5ft~ Max.25ft
Overload Protection	N/A	N/A	N/A
Circuit Breaker Switch	N/A	N/A	N/A
Power Shutdown Protection	N/A	N/A	N/A
Max. Joules Rating	N/A	250 Joules	250 Joules
Max. Spike Current	N/A	4500 Amps	4500 Amps
Max, Spike Voltage	N/A	6000V	6000V
Clamping Voltage (VPR)	N/A	500V (L-N)	500V (L-N)
Response Time	N/A	< 1 nanosecond	< 1 nanosecond
Surge Protection Indicator	N/A	1*Green LED	1*Green LED
Wire Fault Indicator	N/A	N/A	N/A
EMI/ RFI Noise Filter	N/A	N/A	N/A
USB Charger	2 x USB - 2.4A shared	2 x USB - 2.4A shared	2 x USB - 3.9A shared
Phone/Network Protector	N/A	N/A	N/A
Coax/Satellite Protection	N/A	N/A	N/A
Product Dimension	L207.6x W44 x H29mm	L207.6x W44 x H29mm	L207.6x W44 x H29mm